

#3200 "True Grit" Anti-Skid Tape *Stripes & Solids*

Application:

Anti-Slip grit tape products are a fast, easy way to reduce slip and fall accidents in the workplace. Tape will adhere to any clean dry surface including metal, wood, and concrete. Surface is constructed of a aluminum oxide grit compound securely bonded to a vinyl substrate with an aggressive acrylic adhesive. This tape is intended for both indoor and outdoor applications, and the water-proof under normal conditions. Not intended for submerged applications.

PHYSICAL PROPERTIES

- Adhesive – Acrylic Solvent Adhesive
- Carrier – Vinyl (6 mil) with Aluminum Oxide Grit Material (60 Grit)
- Total Thickness – 0.030" (0.762 mm)
- Grit Size –46 Grit
- Liner – Brown Kraft Paper Liner 0.007" (0.18 mm)
- Tape Application – Minimum application temperature 10°C (50°F). Surface must be clean and free from dust, dirt, oil, wax, silicone.
- Cleaning – Clean tape surface with a mild soap and light broom, rinse with fresh water.
- Shelf Life – One year from date of purchase when stored at 70°F, 50% relative humidity.

<u>Property:</u>	<u>Test Method:</u>	<u>Measurement:</u>
<i>PVC Film</i>		
Thickness	PSTC-33	0.15mm (6 mils)
Tensile Strength MD	ASTM-D638	4.2 kg/15mm (15.4lbs/inch)
Tensile Strength CD	ASTM-D638	3.1 kg/15mm (11.4 lbs/inch)
Elongation	ASTM-D638	200% +/- 25%
<i>Acrylic Adhesive</i>		
Dry Coat Weight	PSTC-33	44.4 g/m ²
Coating Thickness	PSTC-33	0.06mm(0.0023")
Residual Solvent		> 0.5 %
Tack	PSTC-6	20 cm (8 inch)
Shear Resistance	PSTC-7	24 hours (1" x 1" @ Kg)
180 Peel Adhesion	PSTC-1	2.5 Kg/25 mm (5 lb/inch)
Operational Temp.		(-10°C to 60°C) -14°F to 140°F
Min Application Temp		10°C (50°F)

Physical characteristics shown are averages from tests recommended by our own procedures. A particular roll may vary slightly from these averages. The buyer should determine the suitability for his own use.

ELECTRO TAPE SPECIALTIES, INC, 13221 BYRD DRIVE, ODESSA, FL 33556
TOLL FREE: (800) 999-2218 TEL: (813) 920-2218 FAX: (813) 920-2272

72018TL

P R O D U C T D A T A