

510 2 Mil Aluminum Foil Tape

DESCRIPTION

A 2 mil (50 micron) high strength aluminum foil coated with an aggressive, high temperature acrylic adhesive system.

FEATURES

The foil conforms well to both fibrous and sheet metal ducts, providing an excellent vapor seal. The malleable foil also conforms well around corners and to irregular surfaces. Coated with a special cold weather acrylic pressure sensitive adhesive system which combines superior quick stick at normal temperatures with superior low temperature performance below freezing – this is the ultimate in cold weather tapes. Recommended for use at normal and elevated temperatures also.

APPLICATION

Primarily used for vapor sealing fiberglass duct board and sheet metal ducts, can also be used on FSK system.

PHYSICAL PROPERTIES

Total Thickness	3.3 mil
Temperature Resistance	-35°F to 260°F
Minimum Application Temperature	-25°F
Peel Adhesion	60 oz./ in.
Shear Strength	2.2 psi
Tensile Strength	47 lbs. / in.
Elongation	4.4%

SPECIFICATIONS Tape is UL 723 listed

Physical characteristics shown are averages from tests recommended by our own procedures. A particular roll may vary slightly from these averages. The buyer should determine the suitability for his own use.

ELECTRO TAPE SPECIALTIES, INC, 13221 BYRD DRIVE, ODESSA, FL 33556
TOLL FREE: (800) 999-2218 TEL: (813) 920-2218 FAX: (813) 920-2272