

Product Data Sheet

#651-A series

D/S PE Foam Tape (1/32"-1/16"-1/8" Thicknesses)

Tape Construction, Features & Characteristics

Adhesive : Hi Performance Acrylic (Solvent based) adhesive coated on both sides.
Carrier : Crosslinked PE foam (1/8" & 1/16" at 4PCF and 1/32" at 6 PCF).
Liner : 49 lb. bleached glassine paper release liner.

- Excellent Quick stick, even to low energy surfaces.
- Good resistance to humidity, mild acids, oil, and grease.
- Foam has superior conformability and compressibility allowing bonding to textured and irregular surfaces.
- Acrylic adhesive provides good weather ability and aging characteristics.

Technical Data:

- **Thickness** : 1/32" (31 mil) – 1/16"(62mil) – 1/8"(125mil)
- **Peel Adhesion** : PSTC-3 >90 oz. / inch or Foam Tear
- **Shear Strength:** 2.2 psi indefinite
- **Elongation:** 300%
- **Tensile:** 5 lb./inch
- **Heat Resistance** : 176 °F (79°C)
- **Minimum Application Temp:** -10 °F (-23°C)

Applications

- Used for mounting nameplates, signs, small die cast parts, mirrors and for sound and vibration dampening.

Shelf Life is 1 Year from Date of Manufacture when stored in proper conditions.

IMPORTANT NOTICE: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. SUPPLIER can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. The information does not constitute a performance guarantee. Performance of the products may vary with individual applications and the purchaser should satisfy himself prior to use as to the suitability of the product for the particular application. SUPPLIER shall not be liable for damages in excess of the purchase price of its products or for incidental or consequential damages.