



Product Data Sheet

#656

SINGLE SIDED MEDIUM DENSITY PVC FOAM TAPE ~ GRAY

DESCRIPTION

A Medium density Closed Cell PVC foam tape coated on one side with a high performance acrylic adhesive. Carried on a siliconized paper liner. Excellent combination of flexibility and conformability with strength & wear resistance. Excellent weatherability & chemical resistance. It is a clean, waste free substitute for liquid sealants.

APPLICATIONS

- Major application: window glazing
- Used for mounting / fixing molding and emblems to various surfaces.
- Vibration dampening, sealing, seaming, and/or gasketing.

PHYSICAL PROPERTIES

| | |
|--------------------------------|--|
| Foam | PVC |
| Density (Range) | 13 - 17 lb. per cubic foot |
| Force to Compress 25% (Range) | 6.5 – 9.5 psi |
| Compression Deflection (Range) | 4.0 – 6.0 psi |
| Tensile Strength | Minimum 45 psi |
| Color | Gray |
| Adhesive | Water Based Acrylic |
| Adhesion (SST) – ASTM D-1000 | 20min. Dwell: 30-48 oz/inch; 24 hr. Dwell: +80 oz/inch |
| Service Temperature | -40°F to 180°F |
| Release Liner | White Siliconized Paper Liner |

The physical and performance characteristics shown are averages obtained from tests recommended by ASTM, government agencies or our own procedures. A particular roll may vary slightly from these averages and it is recommended that the purchaser determine the suitability for his own purpose.