



Product Data Sheet

#668 Double-sided Non-Woven Tape

Product Description

- Premium grade, double coated, tissue paper tape
- Two sided coating of acrylic-based, pressure sensitive adhesives

Applications

- Usable on a wide variety of surfaces such as metals, cloth, nameplates, envelopes, and plastic decorative sheets
- Applicable in the electronic industry.

Features/Benefits

- High quality and strong holding power acrylic adhesive allows for use on a wide variety of surfaces
- Excellent resistance to heat, weathering and thermal creep
- Heavy-duty release paper allows for easy manual handling
- No known hazards

Technical Performance

Description	Units	Value	Test method
Tape thickness	mm/mils	0.10 / 4.0	PSTC-33
Adhesion to steel	kg/cm, oz/in	0.50 / 45	ASTM D-1000
Cohesion to steel	hrs	4.0	PSTC-7
Elongation at break	%	3.0	PSTC-31
Tensile Strength	kg/cm, lbs/in	1.0 / 5.5	PSTC-31
Service Temp.	°C (°F)	177 °C (350°F)	

Storage Details

- Recommended one-year shelf life from date of dispatch if kept at moderate temperatures and humidity levels

The physical and performance characteristics shown are averages obtained from tests recommended by ASTM, government agencies or our own procedures. A particular roll may vary slightly from these averages and it is recommended that the purchaser determine the suitability for his own purpose.