

# #66692

## 9.2mil SCRIM ACRYLIC TRANSFER TAPE

### DESCRIPTION:

#66692 is an HIGHLY aggressive brown PETP scrim coated on both sides with a water borne modified Acrylic Adhesive. This hand-tearable tape is supplied on a natural siliconized paper release liner. The adhesive system of this double coated tape has excellent tack combined with a high adhesive strength, and will bond well to nearly all materials; even to difficult surfaces like foams, PE and PP films. *The heavy adhesive weight ensures quick grab and hold on highly textured surfaces.* It has excellent temperature, UV, aging, and water vapor resistance. **Special adhesive formulation provides very good anti-migration of plasticizers.**

### APPLICATIONS:

- Used for permanent bonding of various materials such as fabrics, wallboard, plastics – including PVC, metal and wood surfaces.
- Acrylic adhesive provides long term performance.
- Also used to laminate to foams and films – scrim reinforcement provides for improved lay down.

### PHYSICAL PROPERTIES:

Backing	PETP scrim
Adhesive	Modified Acrylic Adhesive
Total Thickness	9.2 mil exclusive of liner
Adhesion	> 120 oz / inch
Temperature Resistance	up to +248°F
Condensation water Resistance	Good
Aging Resistance	Very Good
Softener (Plasticizer) Resistance	Very Good

**NOTE:** The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.