

PRODUCT DATA

ETS # 669B

Double-sided Non Woven Tape ~ BLACK in color

Product Description

- Premium grade, double coated, BLACK tissue paper tape – Use of black tissue along with black adhesive provides for a “lightproof” PSA tape
- Two sided coating of DIFFERENTIAL Tack, Solvent Based Acrylic adhesives ~ Exposed Side has higher adhesion which promotes quick bonding results.

Applications

- “Black-out” Feature makes tape great for foam laminating or converting applications of PSA tapes where light penetration prevention is desired – i.e. gaskets for speakers, back-lit signs, electronics, etc.
- Suitable for Visual Splicing Applications..

Features/Benefits

- High quality and strong holding power acrylic adhesive allows for use on a wide variety of surfaces
- Excellent resistance to heat, weathering and thermal creep

Technical Performance

Description	Units	Value	Test method
Tape thickness	mils	4.3	PSTC-33
Adhesion to steel			
- Exposed side	oz/in	77.0	PSTC-3
- Liner side	“	49.0	“
Tack – Exposed	J. Dow No.	18	J.Dow
- Liner	“	14	“
Shear Strength		> 24 hrs	PSTC-7
Long Term Service Temp.	°C (°F)	-20°C(-4°F) to 80°C(176°F)	
Short Term Service Temp. (max 30 mins)	°C (°F)	-up to 175°C(347°F)	

Storage Details

- Recommended one-year shelf life from date of dispatch if kept at moderate temperatures and humidity levels

The technical information and data obtained from tests are considered representative and should not be used for specification purposes. A particular roll's performance may vary slightly from the average, and it is recommended that the buyer determine the suitability of a product for his own uses through personal tests.