

#691 Double Coated Polyester Tape

DESCRIPTION

A double coated polyester film tape with coated with an aggressive, high tack rubber adhesive. A versatile, cost effective industrial tape which has excellent quick stick and peel adhesion properties for permanent bonding, splicing, joining applications on a wide range of substrates (foams, plastics, poly sheeting, metals, composite materials, smooth fabrics, etc.)

PHYSICAL PROPERTIES

Backing:	Polyester Film, Clear 0.5 mil
Adhesive:	Synthetic Copolymer, Rubber
Liner:	Kraft Paper Liner
Tape Thickness:	3.3 mil
Adhesion to SST:	80 oz/in
Shear Strength:	>8 hours
Minimum Continuous Temperature:	10°F (-12°C)
Maximum Continuous Temperature:	170°F (77°C)
Maximum Intermittent Temperature:	195°F (91°C)

Physical characteristics shown are averages from tests recommended by our own procedures. A particular roll may vary slightly from these averages. The buyer should determine the suitability for his own use.

**ELECTRO TAPE SPECIALTIES, INC, 13221 BYRD DRIVE, ODESSA, FL 33556
TOLL FREE: (800) 999-2218 TEL: (813) 920-2218 FAX: (813) 920-2272**

PRO
DUC
T
D
ATA