

750 Professional ALL Weather Vinyl



DESCRIPTION

Electro 750 is a Professional grade, highly conformable 7.0 mil thick vinyl plastic tape which can be used under all weather conditions and is designed to perform in both Cold and Hot temperature environments range from -12° C/-18° C thru 105° C. This tape has excellent resistance to: acids, alkalies, abrasion, moisture, corrosion and varying weather conditions (i.e.: sunlight). With its memory (elasticity), 7.0 mil thickness and adhesion characteristics, it provides moisture-tight electrical and mechanical protection.

FEATURES

- U.L. & C.S.A. Approved. Meets UL510 requirements.
- Polyvinyl chloride (PVC backing).
- Pressure sensitive (rubber based adhesive).
- Memory (elasticity) of tape allows it to hold tightly & provide pressure without slipping or flagging.
- Compatible with all solid dielectric cable insulations.
- Highly resistant to chemical attack, ultra violet light and physical abuse.
- **Low Lead.**
- **Flame retardant, cold and weather resistant.**
- **TEMPERATURE RANGE:** -12°C (UL standards) & -18°C (CSA standards) to 105°C
- Will not crack, split, slip or flag when exposed to various environments.

APPLICATIONS

- Primary electrical insulation for all wire and cable splices up to 600 volts and 105° C (221° F).
- For wire and cable harnessing.
- Excellent abrasion resistance for high voltage cable splices and termination (forms a protective jacket).

PHYSICAL PROPERTIES

Normal temperature rating – UL	-12°C(UL stand.) & -18°C (CSA stand.) to 105°C
Color / Finish	Black / Glossy
Thickness (ASTM D-1000 78)	7.0 mils
Adhesion to steel (ASTM D-1000 78 72° F)	23 oz/in
Adhesion to backing (ASTM D-1000 78 72° F)	21 oz/in
Tensile (ASTM D-1000 78 72° F)	21 lb/inch
Elongation (ASTM D-1000 78 72° F)	200%
Flammability UL-510/CSA 22.2	no fail
Dielectric at Break (volts)	8750
Resistance to ultraviolet light	Pass
Resistance to alkalies	Excellent

SPECIFICATIONS

Meets AA55089 (supercedes MIL I-HH-595), UL-510 and CSA 22.2

ELECTRO TAPE SPECIALTIES, INC, 13221 BYRD DRIVE, ODESSA, FL 33556
TOLL FREE: (800) 999-2218 TEL: (813) 920-2218 FAX: (813) 920-2272