



**#808HM**  
**Heavy Duty 3mil PP Carton Seal Tape**

**DESCRIPTION**

3 mil premium heavy duty carton sealing tape with high tack, quick grab, synthetic hot melt adhesive.

**APPLICATION**

- For sealing boxes, splicing and other demanding packaging applications subjected to rough shipping conditions or where very high sealing performance is desired.
- Conforms to Specifications: FDA - 21CFR 175.105 / CID A-A-1684B.

**PHYSICAL PROPERTIES**

Total Thickness	3.0 mil
Film Thickness	50μ (BOPP)
Adhesive	Synthetic Rubber Resin
Tensile Strength (ASTM D3330)	33.1 lbs. / in.
Elongation at Break (ASTM D3759)	140 %
180° Peel Adhesion (ASTM D3759)	47.7 oz. / in.
Holding Power (ASTM D3654)	> 30 hours
Application Temperature	35°F to 120°F
Operating Temperature	-10°F to 140°F

Physical characteristics shown are averages from tests recommended by our own procedures. A particular roll may vary slightly from these averages. The buyer should determine the suitability for his own use.

**ELECTRO TAPE SPECIALTIES, INC, 13221 BYRD DRIVE, ODESSA, FL 33556**  
**TOLL FREE: (800) 999-2218 TEL: (813) 920-2218 FAX: (813) 920-2272**