



Product Data Sheet

145 PE Tape

APPLICATIONS

- For stucco and plaster masking applications.
- For outdoor masking.
- Sunlight (UV) exposure applications.
- For outdoor applications where the tape is required to perform over an extended period of time up to 30 days but will offer easy, residue-free removal.

FEATURES & BENEFITS

- Specially designed adhesive virtually eliminates residue even after extended exposure.
- High quality adhesive holds even on rough surfaces. Very confirmable.
- Easy unwind
- Film & adhesive construction allow for cold weather performance – much better than standard duct tapes

PRODUCT DESCRIPTION

- Single Coated Construction
- Backing – Durable low density Polyethylene Film
- Adhesive – Rubber based adhesive

PHYSICAL PROPERTIES

- | | |
|---------------------------------|------------------------------|
| • Adhesion to Backing | 35 oz./inch |
| • Adhesion To Steel | 60 oz./inch |
| • Total Tape Thickness | 7.0 mil |
| • Adhesive Thickness | 2.5 mil |
| • Tensile Strength | 20 lbs./inch |
| • Elongation | 90% |
| • Color | Red, White (serrated), Black |
| • Application Temperature Range | 55°F to 100°F |
| • Service Temperature Range | 25°F to 160°F |

The physical and performance characteristics shown are averages obtained from tests recommended by ASTM, government agencies or our own procedures. A particular roll may vary slightly from these averages and it is recommended that the purchaser determine the suitability for his own purpose.

TWL2014