

150C Vinyl Marking Tape ~ Clean Room

APPLICATION

The #150C is a premium quality vinyl tape. General tape construction is designed for industrial, commercial and recreational safety marking applications. Used to identify aisles, steps, equipment and potentially hazardous areas. Color satisfies O.S.H.A. marking requirements. **150C is specifically designed for CLEAN ROOM applications as it is wound onto a plastic core and individually wrapped** with additional bag packaging to ensure minimal dust or dirt or other particular contaminants in tape. Classification ISO 5.

FEATURES

- Sturdy 6-mil vinyl – will hold up under the heaviest duty wear and traffic conditions.
- Highly conformable to all surfaces.
- Abrasion resistant and non-fading.
- Resists oil, grease and many solvents.
- Easily dispensed, either automatically or by hand, for quick and secure installation.
- Immersion in water will not cause disintegration or loosening.

PHYSICAL PROPERTIES

Backing Material	Vinyl Film
Adhesive	Natural Rubber Resin
Color	White
Total Tape Thickness	6 mil
Tensile Strength	18 lbs. / in.
Unwind @ 150 FPM	80 oz. / in.
Elongation	160 %
Adhesion To Steel	30 oz. / in.
Government Specification	PPP-T-66D, TYPE 1
Operating Temperature Range	40°F to 176°F

The physical and performance characteristics shown are averages obtained from tests recommended by ASTM, government agencies or our own procedures. A particular roll may vary slightly from these averages and it is recommended that the purchaser determine the suitability for his own purpose.