

255N SERIES INDUSTRIAL GRADE MASKING TAPE

DESCRIPTION

A beige, conformable, semi-bleached crepe paper masking tape coated with pressure-sensitive natural rubber adhesive. Capable of withstanding bake temperatures up to 180°F (82°C) for up to one hour and/or exposure to ultra-violet (UV) light for up to five hours. Offers consistent conformability and tensile strength for general purpose bundling, protecting, and various industrial applications.



APPLICATIONS

Interior paint masking, spray painting (air-dry) autos, boats, etc., boat manufacturing (fiberglass), silk screening, mail rooms, marble manufacturing (man-made), golf club shaft (build-up), carpet pad / pad splicing, freezer tape, and light bundling, packaging, splicing and tabbing.

GOVERNMENT COMPLIANCE

PPP-T-42C, Type I UU-T-106, Type I C.I.D. A-A-883, Type I

TECHNICAL PROPERTIES

Property	Nominal Value	Test Method
Backing	Crepe Paper	
Adhesive	Natural/Synthetic Rubber	
Adhesion to Steel	31 oz/in of width (8.5 N/25mm)	PSTC-101
Tensile Strength	20 lbs/in of width (87.8 N/25mm)	PSTC-131
Elongation	12% (at break)	PSTC-131
Total Thickness	6.0 mils (0.15mm)	PSTC-133
Quick Stick to Steel	14 oz/in of width (3.8 N/25mm)	PSTC-5
Color	Beige	

*Physical characteristics shown are averages from tests recommended by our own procedures.
A particular roll may vary slightly from these averages. The buyer should determine the suitability for his own use.*