

515 FSK Aluminum Foil Facing Tape

DESCRIPTION

Tridirectionally reinforced with 2 X 3 sq. / in. fiberglass scrim, U.L. listed foil / scrim / kraft lamination. This tape conforms well to both fibrous ductboard and blankets. Coated with a special cold weather, acrylic, pressure sensitive adhesive system that combines superior quick stick at normal temperatures with superior low temperature performance below freezing, this is the ultimate in cold weather tapes. Recommended for use at normal and elevated temperatures also.

APPLICATION

Primarily used as a vapor seal on FSK faced fiberglass ductboard and blanket systems.

PHYSICAL PROPERTIES

Total Thickness	6.5 mil
Peel Adhesion	70 oz. / in.
Shear Indefinite @	2 psi
Tensile Strength	40 lbs. / in.
Elongation	2 %
High Temperature Resistance	260°F
Low Temperature Sealing	-25°F
WVTR	.02 U.S. Perms
Flame Spread	5
Smoke Developed	10

Meets ASTM C 1136
Conforms to British Standard Class 1 BS 476: Part 7

Physical characteristics shown are averages from tests recommended by our own procedures. A particular roll may vary slightly from these averages. The buyer should determine the suitability for his own use.

TWL916

**ELECTRO TAPE SPECIALTIES, INC, 13221 BYRD DRIVE, ODESSA, FL 33556
TOLL FREE: (800) 999-2218 TEL: (813) 920-2218 FAX: (813) 920-2272**